

## Impact Sprinkler Male

### ■ LM-9721

Medium flow agricultural plastic impact sprinkler, suitable for general field use with solid set irrigation system. It is suitable for irrigating mixed crops, orchards, market gardens, golf courses and protecting the plants against frost.

#### ■ FEATURES

- High impact heavy duty plastic materials, UV protection.
- Nickel-plated steel counterweights inserted into the arms.
- Its stainless steel springs and teflon washers guarantee excellent rotation even at low pressures (1.5 bar).
- 3/4" NPT male connection
- Flow rates: 1200 to 2500 l/hr (5.3 - 11 gpm)
- Recommended pressure: 2 to 3 bar (29 - 43 psi)
- Diameter: 24 to 32 m (79 - 105 ft)
- Factory warranty for a period of one year.



Nozzle	1.5 bar		2.0 bar		2.5 bar		3.0 bar		3.5 bar	
mm	M <sup>3</sup> /h	R(m)	M <sup>3</sup> /h	R(m)	M <sup>3</sup> /h	R(m)	M <sup>3</sup> /h	R(m)	M <sup>3</sup> /h	R(m)
3.8 x 2.3	1.02	15.5	1.20	15.6	1.26	15.8	1.36	16.0	1.44	16.5
4.2 x 3.2	1.44	15.8	1.68	16.0	1.86	16.3	2.04	16.5	2.26	17.0
5.0 x 4.2	1.92	16.0	2.14	16.2	2.46	16.5	2.74	17.0	2.94	17.5