

MAXPOWER®

Wobbler Sprinkler

■ HIGH ANGLE

The wobbler model uses off-center rotary action technology. It provides an extremely uniform and instantaneous application pattern over a large area at lower pressures, and with very low evaporative loss.



- Counter-balance reduces vibration for a smooth, stable performance.
- One moving part-which translates to longer life.
- 1/2" or 3/4" NPT male connection
- Flow rates: 177 to 1583 l/hr (0,78 - 6,97 gpm)
- Pressure: 0.69 to 1.72 bar (10 - 25 psi)
- Diameter: 11.1 to 16.9 m (36,5 - 55,5 ft)
- Stream height: 0,8 to 1,7 m (2,5 - 5,5 ft)
- Low wind drift and evaporative loss at low pressures.
- Color-coded nozzles for easy size identification.
- Material: Made of Polypropylene, UV protection.
- Factory warranty for a period of one year.

New model with 9 outlets; produces finer droplets, less erosion and better absorption. Greater protection against the impact of water. Recommended for maintenance and recovery of pastures and forages.



CLASSIC MODEL



NEW MODEL

Water Pressure (bar)			0,6		1,03		1,38		1,72	
Nozzle color/num	d(mm)		Flow Rate (l/h)	Diameter (m)	Flow Rate (l/h)	Diameter (m)	Flow Rate (l/h)	Diameter (m)	Flow Rate (l/h)	Diameter (m)
 #06	2,38		177	11,1	216	12,5	250	13,7	279	14,0
 #07	2,78		241	12,2	295	14,2	341	14,3	382	15,4
 #08	3,18		318	12,8	388	14,2	450	14,3	502	15,7
 #09	3,57		409	13,4	500	14,3	577	15,4	645	16,0
 #10	3,97		504	13,6	618	14,9	713	15,4	797	16,3
 #11	4,37		611	13,6	749	15,4	865	15,7	968	16,5
 #12	4,76		734	14,0	899	15,4	1038	15,9	1161	16,6
 #13	5,16		863	14,2	1056	15,6	1222	16,0	1365	16,9
 #14	5,56		999	14,3	1224	15,6	1415	16,2	1583	16,9